

SOLVENT DISTILLATION EQUIPMENT

LS Series[†]

Two stage Distillation Process:
 1. Heats solvent to a vapor state
 2. Cools and converts vapor to a pure, reusable liquid product



LS-Jr.-E

- Small shop applications

Process rate	3-5 gal/shift*
Boiling Range	100 - 300°F

FTI's Unique Features:

Eliminate or reduce solvent-based waste

• 99+% pure, reusable solvent

• Patented design and encapsulated heating element

• Lifetime warranty on heater element

• CSA approved

• Teflon[®] coated boiling chamber for quick clean up

• Stilbags or Stilpans available to aid in residue removal

• Solvent boiling range 100 to 300°F.
 Increases to 500°F with vacuum assist.
 All units vacuum capable.

• Technical support from FTI via toll free number



LS-15IIE

- Automatic cycle control
- Less operator involvement

Process rate	15 gal/shift*
Boiling Range	100 - 300°F



LS-55E with JetVac

- Safely recovers high boiling solvents with JetVac option

Process rate	55 gal/shift*
Boiling Range	100 - 500°F



LS-55STE

- Higher volume system utilizes in-plant steam

Process rate	110 gal/shift*
Boiling Range	100 - 300°F

*Varies with application

†Equipment appearance may vary slightly from photo



Before



After

FLOW TECH
CORPORATION



(Toll Free) 877.375.1290
 7601 Stadium Drive Kalamazoo, MI 49009
flowtechfilters.com